

WATER HEATERS





LEO FL



10–53 kW
800–4200 m³/h

- light, functional design
- aesthetic finishing
- durability
- rotary 3D-console

PAGE 10

LEO FB



3–100 kW
150–8500 m³/h

- most economic
- easy and simple mounting
- 3D-console and other accessories
- considerable weight reduction*
- Leo FB 15 M-type equipped with energy-saving EC fan.

* in relation to common steel casing

PAGE 14

LEO FS



5–19 kW
230–1750 m³/h

- installation covered by the casing
- available with mixing chamber - KMFS
- ideal for elegant buildings
- M type units equipped with EC fan (electronically commutated)

PAGE 16

PAGE 25



LEO
FX

LEO
KM

LEO
D



10–65 kW

700–4500 m³/h

Special purpose devices:

- EX - explosion-proof
- INOX - food industry
- EL - electrical heater
- AGRO - agricultural buildings

9–51 kW

540–3200 m³/h

- simplest mechanical ventilation
- automatic control and anti-freeze protection*

* optional equipment

-

5100 m³/h

- maintains warm air within the comfort zone
- max. mounting height 12 m
- reduces heat losses

LEO
EX

PAGE 18

LEO
INOX

PAGE 19

LEO
EL

PAGE 19

LEO
AGRO

PAGE 20

PAGE 24

PAGE 28

intelligent air flow